

精度:

直徑	間格	長度	直徑精度	真圓度公差
0.05~0.09	0.01	5~10	±0.5um	0.5um
0.10~0.19	0.01	20	±0.5um	0.5um
0.20~0.49	0.01	40	±1um	0.8um
0.50~10.00	0.01	50	±1um	0.8um
10.01~20.00	0.01	50	±1.5um	1.6um
20.00~30.00	0.01	50	±1.5um	1.6um

針規為孔的標準化檢測的必備檢具,用於檢查位置,測量孔的尺寸,檢查兩孔距,也可作通止規及測量孔的深度用。



55110

GBE

高速鋼針規 High Speed Steel Pin Gauge

間格尺寸為0.01mm

訂購編號 Order No.	型號 Model	公稱尺寸	支/盒	重量 N.W.
55110-0510	GB0510E	0.50, 0.51, 0.52~1.00	51	1.11kg
55110-1015	GB1015E	1.00, 1.01, 1.02~1.50	51	1.13kg
55110-1520	GB1520E	1.50, 1.51, 1.52~2.00	51	1.15kg
55110-2025	GB2025E	2.00, 2.01, 2.02~2.50	51	1.19kg
55110-2530	GB2530E	2.50, 2.51, 2.25~3.00	51	1.23kg
55110-3035	GB3035E	3.00, 3.01, 3.02~3.50	51	1.27kg
55110-3540	GB3540E	3.50, 3.51, 3.52~4.00	51	1.33kg
55110-4045	GB4045E	4.00, 4.01, 4.02~4.50	51	1.39kg
55110-4550	GB4550E	4.50, 4.51, 4.52~5.00	51	1.47kg
55110-5055	GB5055E	5.00, 5.01, 5.02~5.50	51	1.55kg
55110-5560	GB5560E	5.50, 5.51, 5.52~6.00	51	1.63kg
55110-6065	GB6065E	6.00, 6.01, 6.02~6.50	51	1.73kg
55110-6570	GB6570E	6.50, 6.51, 6.52~7.00	51	1.83kg
55110-7075	GB7075E	7.00, 7.01, 7.02~7.50	51	1.95kg
55110-7580	GB7580E	7.50, 7.51, 7.52~8.00	51	2.07kg
55110-8085	GB8085E	8.00, 8.01, 8.02~8.50	51	2.19kg
55110-8590	GB8590E	8.50, 8.51, 8.52~9.00	51	2.33kg
55110-9095	GB9095E	9.00, 9.01, 9.02~9.50	51	2.47kg
55110-95100	GB95100E	9.50, 9.51, 9.52~10.00	51	2.63kg

※直徑精度 ± 0.5 μ, ± 0.3 μ 均可接受定制。

